



kaleidescape™

# Kaleidescape Movie Player

KPLAYER-2500



- **Elegant 1U design**
- **Downloadable designs, modules and programs available for integration with Crestron and AMX touch panels**
- **Downloadable files available for popular universal remote controls**

The Kaleidescape Movie Player is a high-performance audio/video component designed to play back movies and music in a Kaleidescape System. The elegant 1U low-profile chassis is designed to be rack mounted.

The Kaleidescape Movie Player can play HD and DVD movies from a Kaleidescape Server to a display device in the digital domain without any analog processing. Dolby™ Digital, DTS, MPEG, and PCM audio formats are fully supported. The High-Definition Multimedia Interface (HDMI™) and component video connections deliver reference-quality video.

The Kaleidescape Movie Player can be integrated with control systems via an extensive bi-directional control protocol over RS-232 or TCP/IP. IR control is also available. Control protocol and configuration options enable seamless integration with and automatic control of audio and video processors, movie projectors, display devices, control systems, lighting systems, screen-masking systems, and audio systems.



## KPLAYER-2500 Specifications

### Video Outputs

- HDMI (w/HDCP™)
- Component YPbPr (BNC)
- S-Video
- Composite (BNC)

### Video Output Formats

- NTSC 480i, 480p
- PAL 576i, 576p
- High-definition 720p, 1080i at 50 and 60 Hz
- Progressive scan using DCDi by Faroudja

### Audio Outputs

- HDMI
- Digital, coaxial (BNC) and optical (TosLink)
- Analog stereo (RCA)

### Audio Output Formats

- Dolby
- DTS
- MPEG Audio
- PCM

### Connections

- 100Base-TX Ethernet (RJ45)
- RS-232 for control systems (DB-9 male)
- IR front-bezel window, IR-in 1/8" mini jack

### Dimensions (w x h x d)

- 17.2 in x 1.7 in x 13.8 in  
(43.7 cm x 4.3 cm x 35 cm)
- 1 rack unit

### Weight

- 11 pounds (5 kg)

### Power

- 100-240V 50-60Hz, 0.5A

### Environmental

- Operating: 5 to 40°C (41 to 104°F)
- Storage: -20 to 60°C (-4 to 140°F)
- Relative humidity: 5% to 90%, non-condensing

### Certifications

- ENTELA (IEC 60065, CSAC22.2 E560065, UL60065)
- Macrovision™
- Dolby
- HDMI



kaleidescape

Kaleidescape, Inc.  
520 Logue Avenue  
Mountain View, CA 94043 USA  
+1 (650) 625-6100  
Toll Free within the US: (888) 352-5343  
[www.kaleidescape.com](http://www.kaleidescape.com)