

ENCORE

KALEIDESCAPE DISC SERVER



kaleidescape



AT A GLANCE:

- Perfect for a collection of movies on DVDs and Blu-ray discs
- Holds up to 320 discs
- Compatible with Kaleidescape Alto movie player

KALEIDESCAPE DISC SERVER LETS YOU BROWSE AND PLAY YOUR DVDS AND BLU-RAY DISCS.

The Kaleidescape Disc Server is the perfect solution for a collection of DVDs and Blu-ray discs. It's a great way to select and play a movie, without the inconvenience of having to find and insert the disc.

The Disc Server connects to your home network and becomes part of your Kaleidescape Encore system. You can browse and play your movies on any Kaleidescape Alto movie player.

Discs in the Disc Server appear on the onscreen display, along with the movies you've downloaded from the Kaleidescape Movie Store. You can play a disc in the same way that you play a downloaded movie.

KALEIDESCAPE DISC SERVER



DIMENSIONS

- 17.5in × 8.8in × 21.9in (W × H × D)
(44.5cm × 22.4cm × 55.6cm)

WEIGHT

- 38lbs (17.2kg) empty
- 49lbs (22.2kg) fully loaded with discs

POWER

- Max consumption: 46W
- Typical: 34W
- Standby: 32W
- 100–240V, 50–60Hz universal input

NETWORK

- 100Base-TX/1000Base-T Ethernet
(RJ45 connector)

OTHER CONNECTION

- USB 2.0 (reserved)

RACK MOUNT

- Rack ears included for mounting in a
19in rack, 5U space

ENVIRONMENT

- Operating temperature: 41 to 95°F
(5 to 35°C)
- Storage temperature: -4 to 140°F
(-20 to 60°C)
- Relative humidity: 20% to 80%
non-condensing
- Maximum operating altitude:
10,000ft (3,048m)
- Heat output: 160 BTU/hr (46W) max
- Airflow: 7 CFM (12 m³/hr) max

VENTILATION

- Minimum 1in (2.5cm) space at the front
- Minimum 2in (5cm) space at the rear

DISC MEDIA

- Blu-ray disc, BD-R, BD-RE
- DVD, DVD-R, DVD-RW, DVD+R,
DVD+RW
- Standard 12cm (4.7in) diameter discs

CAPACITY

- 320 discs

REGIONAL PLAYBACK CONTROL

Each Disc Server has a DVD region code which can be changed up to four times. A DVD that matches the region code configured for the Disc Server can be played by any movie player in the system.

CERTIFICATIONS

- CSA 60950-1
- IEC 60950-1
- FCC CLASS B
- CE
- EAC
- RoHS Compliant

LIMITED WARRANTY

- 3 years (extendable)

